

View Online at <https://aerobasegroup.com/nsn/5315-01-357-7898>

Handle Length:

2.345 inches

Shank Diameter:

Between 0.4970 inches and 0.4985 inches

Detent Quantity:

2

Lanyard Length:

12.000 inches

Actuation Method:

Push button

Grip Length:

Between 4.000 inches and 4.020 inches

Actuation Type:

Push

Shear Strength:

32800 double pound

Shoulder To Head End Distance:

1.600 inches

Pin Attachment Type:

Cable lanyard w/terminations

Detent To Tapered End Distance:

Between 0.430 inches and 0.460 inches

Special Features:

Hook or ring attached

Material:

Steel comp 4130 shanksteel comp 4130 spindle

Material Specification:

Mil-t-6736 military specification single material response shank or mil-s-6758 military specification single material response shankmil-t-6736 military specification single material response spindle or mil-s-6758 military specification single material response spindle

Surface Treatment:

Cadmium shank and chromate shankcadmium spindle and chromate spindle

Surface Treatment Specification:

Qq-p-416, type 2, cl 2 federal specification single treatment response shankqq-p-416, type 2, cl 2 federal specification single treatment response spindle

Style Designator:

T handle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A212a0

Mil-std (military Standard):

Mil-t-6736 spec.