

View Online at <https://aerobasegroup.com/nsn/5315-01-359-8969>

Head Diameter:

1.300 inches

Shank Diameter:

Between 0.7460 inches and 0.7490 inches

Ring Handle Diameter:

1.580 inches

Detent Quantity:

2

Actuation Method:

Push button

Grip Length:

Between 2.600 inches and 2.620 inches

Actuation Type:

Push

Hardness Rating:

40.0 rockwell c shank

Shear Strength:

83200 double pound

Shoulder To Head End Distance:

1.680 inches

Pin Attachment Type:

Link or ring

Detent To Tapered End Distance:

0.887 inches

Material:

Aluminum alloy headsteel comp 630 shank or steel comp 632 shanksteel comp 630 spindle or steel comp 632 spindle

Material Specification:

Ams 5643 assn standard 1st material response shank or ams 5657 assn standard 2nd material response shankams 5643 assn standard 1st material response spindle or ams 5657 assn standard 2nd material response spindle

Surface Treatment:

Passivate shankpassivate spindle

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response shankqq-p-35 federal specification single treatment response spindle

Style Designator:

Ring handle

Specification Data:

80205-nas1361 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A212a0