

View Online at <https://aerobasegroup.com/nsn/5315-01-360-1815>

Head Diameter:

0.750 inches

Shank Diameter:

Between 0.3720 inches and 0.3745 inches

Ring Handle Diameter:

1.150 inches

Detent Quantity:

2

Actuation Method:

Push button

Grip Length:

Between 2.500 inches and 2.520 inches

Actuation Type:

Pull and push

Hardness Rating:

40.0 rockwell c shank 40.0 rockwell c spindle

Shear Strength:

20700 double pound

Shoulder To Head End Distance:

1.290 inches

Pin Attachment Type:

Link and ring

Detent To Tapered End Distance:

0.510 inches

Material:

Aluminum alloy 2017 head or aluminum alloy 2024 head or aluminum alloy 7075 head steel comp 630 shank or steel comp 632 shank steel comp 630 spindle or steel comp 632 spindle

Material Specification:

Qq-a-225/5 federal specification 1st material response head or qq-a-225/6 federal specification 2nd material response head or qq-a-225/9 federal specification 3rd material response head ams 5643 assn standard 1st material response shank or ams 5657 assn standard 2nd material response shank ams 5643 assn standard 1st material response spindle or ams 5657 assn standard 2nd material response spindle

Surface Treatment:

Anodize head passivate shank passivate spindle

Surface Treatment Specification:

Mil-a-8625 military specification single treatment response head qq-p-35 federal specification single treatment response shank qq-p-35 federal specification single treatment response spindle

Style Designator:

Ring handle

Specification Data:

80205-nas1356 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Fig:

A212a0

Mil-std (military Standard):

Mil-a-8625 spec.