

View Online at <https://aerobasegroup.com/nsn/5315-01-360-1817>

**Head Diameter:**

0.940 inches

**Shank Diameter:**

Between 0.4970 inches and 0.4995 inches

**Ring Handle Diameter:**

1.280 inches

**Detent Quantity:**

2

**Actuation Method:**

Push button

**Grip Length:**

Between 2.500 inches and 2.520 inches

**Actuation Type:**

Pull and push

**Shear Strength:**

36900 double pound

**Shoulder To Head End Distance:**

1.340 inches

**Pin Attachment Type:**

Link and ring

**Detent To Tapered End Distance:**

0.590 inches

**Material:**

Aluminum alloy 2017 head or aluminum alloy 2024 head or aluminum alloy 7075 headsteel comp 630 shank or steel comp 632 shanksteel comp 630 spindle or steel comp 632 spindle

**Material Specification:**

Qq-a-225/5 federal specification 1st material response head or qq-a-225/6 federal specification 2nd material response head or qq-a-225/9 federal specification 3rd material response head

**Surface Treatment:**

Anodize headpassivate shankpassivate spindle

**Surface Treatment Specification:**

Mil-a-8625 military specification single treatment response headqq-p-35 federal specification single treatment response shankqq-p-35 federal specification single treatment response spindle

**Style Designator:**

Ring handle

**Specification Data:**

80205-nas1358 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A212a0

**Mil-std (military Standard):**

Mil-a-8625 spec.