

View Online at <https://aerobasegroup.com/nsn/5315-01-360-1817>

Head Diameter:

0.940 inches

Shank Diameter:

Between 0.4970 inches and 0.4995 inches

Ring Handle Diameter:

1.280 inches

Detent Quantity:

2

Actuation Method:

Push button

Grip Length:

Between 2.500 inches and 2.520 inches

Actuation Type:

Pull and push

Shear Strength:

36900 double pound

Shoulder To Head End Distance:

1.340 inches

Pin Attachment Type:

Link and ring

Detent To Tapered End Distance:

0.590 inches

Material:

Aluminum alloy 2017 head or aluminum alloy 2024 head or aluminum alloy 7075 headsteel comp 630 shank or steel comp 632 shanksteel comp 630 spindle or steel comp 632 spindle

Material Specification:

Qq-a-225/5 federal specification 1st material response head or qq-a-225/6 federal specification 2nd material response head or qq-a-225/9 federal specification 3rd material response head

Surface Treatment:

Anodize headpassivate shankpassivate spindle

Surface Treatment Specification:

Mil-a-8625 military specification single treatment response headqq-p-35 federal specification single treatment response shankqq-p-35 federal specification single treatment response spindle

Style Designator:

Ring handle

Specification Data:

80205-nas1358 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A212a0

Mil-std (military Standard):

Mil-a-8625 spec.