

View Online at <https://aerobasegroup.com/nsn/5315-01-360-3230>

**Head Diameter:**

0.750 inches

**Shank Diameter:**

Between 0.3720 inches and 0.3745 inches

**Ring Handle Diameter:**

1.150 inches

**Detent Quantity:**

2

**Actuation Method:**

Push button

**Grip Length:**

Between 4.000 inches and 4.020 inches

**Actuation Type:**

Pull and push

**Shear Strength:**

20700 double pound

**Shoulder To Head End Distance:**

1.290 inches

**Pin Attachment Type:**

Link and ring

**Detent To Tapered End Distance:**

0.510 inches

**Material:**

Aluminum alloy 2017 head or aluminum alloy 2024 head or aluminum alloy 7075 headsteel comp 630 shank or steel comp 632 shanksteel comp 630 spindle or steel comp 632 spindle

**Material Specification:**

Qq-a-225/5 federal specification 1st material response head or qq-a-225/6 federal specification 2nd material response head or qq-a-225/9 federal specification 3rd material response headams 5643 assn standard 1st material response shank or ams 5657 assn standard 2nd material response shankams 5643 assn standard 1st material response spindle or ams 5657 assn standard 2nd material response spindle

**Surface Treatment:**

Anodize headpassivate shankpassivate spindle

**Surface Treatment Specification:**

Mil-a-8625 military specification single treatment response headqq-p-35 federal specification single treatment response shankqq-p-35 federal specification single treatment response spindle

**Style Designator:**

Ring handle

**Specification Data:**

80205-nas1356 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

**Mil-std (military Standard):**

Mil-a-8625 spec.