

View Online at <https://aerobasegroup.com/nsn/5315-01-360-8767>

Head Diameter:

0.950 inches

Shank Diameter:

Between 0.4970 inches and 0.4995 inches

Ring Handle Diameter:

1.348 inches

Detent Quantity:

2

Actuation Method:

Push button

Grip Length:

Between 4.200 inches and 4.220 inches

Actuation Type:

Push

Hardness Rating:

40.0 rockwell c shank 54.0 rockwell c detent and 64.0 rockwell c detent

Shoulder To Head End Distance:

1.580 inches

Pin Attachment Type:

Hook or ring

Detent To Tapered End Distance:

0.530 inches

Material:

Steel comp 630 shank or steel comp 632 shank steel comp 630 spindle or steel comp 632 spindle

Material Specification:

Ams 5643 assn standard 1st material response shank or ams 5520 federal standard all material responses shank or ams 5657 assn standard 2nd material response shank ams 5643 assn standard 1st material response spindle or ams 5520 assn standard 2nd material response spindle or ams 5657 assn standard 2nd material response spindle

Surface Treatment:

Passivate shank passivate spindle

Style Designator:

Ring handle

Specification Data:

80205-nas1338 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A212a0