

View Online at <https://aerobasegroup.com/nsn/5315-01-361-9913>

**Shank Diameter:**

Between 0.1870 inches and 0.1895 inches

**Button Handle Diameter:**

1.200 inches

**Detent Quantity:**

2

**Actuation Method:**

Push button

**Grip Length:**

Between 0.600 inches and 0.620 inches

**Actuation Type:**

Push

**Shoulder To Head End Distance:**

1.550 inches

**Pin Attachment Type:**

Ring

**Detent To Tapered End Distance:**

0.380 inches

**Material:**

Steel comp 4130 shank or steel comp 4135 shanksteel comp 8630 spindle and steel comp 4130 spindle

**Material Specification:**

Mil-s-6758 military specification 1st material response shank or mil-t-6735 military specification 2nd material response shank or mil-t-6736 military specification 1st material response shankmil-t-6732 military specification 1st material response spindle or mil-s-6758 military specification 2nd material response spindle

**Surface Treatment:**

Cadmium and chromate

**Surface Treatment Specification:**

Qq-p-416, ty2, cl2 federal specification single treatment response

**Style Designator:**

Button

**Specification Data:**

80205-nas1333 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A212a0

**Mil-std (military Standard):**

Mil-s-6758 spec.