

View Online at <https://aerobasegroup.com/nsn/5315-01-364-4464>

**Shank Diameter:**

Between 0.1870 inches and 0.1895 inches

**Button Handle Diameter:**

1.200 inches

**Detent Quantity:**

2

**Actuation Method:**

Push button

**Grip Length:**

Between 0.700 inches and 0.720 inches

**Actuation Type:**

Push

**Hardness Rating:**

40.0 rockwell c shank 40.0 rockwell c spindle

**Shear Strength:**

5150 double pound

**Shoulder To Head End Distance:**

1.490 inches

**Pin Attachment Type:**

Ring

**Detent To Tapered End Distance:**

0.380 inches

**Material:**

Aluminum alloy 2017 head or aluminum alloy 2024 head or aluminum alloy 7075 head steel comp 630 shank or steel comp 632 shank steel comp 630 spindle or steel comp 632 spindle

**Material Specification:**

Qq-a-225/5 federal specification 1st material response head or qq-a-225/6 federal specification 2nd material response head or qq-a-225/9 federal specification 3rd material response head ams 5643 assn standard 1st material response shank or ams 5657 assn standard 2nd material response shank ams 5643 assn standard 1st material response spindle or ams 5657 assn standard 2nd material response spindle

**Surface Treatment:**

Passivate shank passivate spindle

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response shank qq-p-35 federal specification single treatment response spindle

**Style Designator:**

Button

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A212a0