

View Online at <https://aerobasegroup.com/nsn/5315-01-365-3311>

Shank Diameter:

Between 0.8720 inches and 0.8735 inches

Button Handle Diameter:

Between 2.120 inches and 2.250 inches

Detent Quantity:

2

Actuation Method:

Push button

Grip Length:

Between 3.600 inches and 3.620 inches

Actuation Type:

Push

Shear Strength:

100000 double pound

Shoulder To Head End Distance:

1.985 inches

Pin Attachment Type:

Hook and ring

Detent To Tapered End Distance:

Between 0.720 inches and 0.760 inches

Material:

Aluminum alloy 2024 handle or aluminum alloy 2017 handlesteel comp 4130 shanksteel comp 4130 spindle

Material Specification:

Qq-a-225/6 federal specification 1st material response handle or qq-a-225/5 federal specification 2nd material response handlemil-s-6758 military specification single material response shankmil-s-6758 military specification single material response spindle

Surface Treatment:

Anodize handlecadmium shank and chromate shankcadmium spindle and chromate spindle

Surface Treatment Specification:

Mil-a-8625 military specification single treatment response handleqq-p-416, type 2 federal specification single treatment response shankqq-p-416, type 2 federal specification single treatment response spindle

Style Designator:

Button

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A212a0

Mil-std (military Standard):

Mil-s-6758 spec.