

View Online at <https://aerobasegroup.com/nsn/5315-01-366-1414>

**Shank Diameter:**

Between 0.9970 inches and 0.9985 inches

**Button Handle Diameter:**

Between 1.175 inches and 2.120 inches

**Detent Quantity:**

2

**Actuation Method:**

Push button

**Grip Length:**

Between 3.700 inches and 3.720 inches

**Actuation Type:**

Push

**Hardness Rating:**

40.0 rockwell c shank 40.0 rockwell c spindle

**Shear Strength:**

131000 double pound

**Shoulder To Head End Distance:**

1.490 inches

**Pin Attachment Type:**

Link or ring

**Detent To Tapered End Distance:**

Between 0.860 inches and 0.890 inches

**Material:**

Steel comp 4130 shank or steel comp 8740 shank steel comp 4130 spindle or steel comp 8740 spindle

**Material Specification:**

Mil-t-6736 military specification 1st material response shank or mil-s-6758 military specification 2nd material response shank mil-t-6736 military specification 1st material response spindle or mil-s-6758 military specification 2nd material response spindle

**Surface Treatment:**

Passivate shank passivate spindle

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response shank qq-p-35 federal specification single treatment response spindle

**Style Designator:**

Button

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A212a0

**Mil-std (military Standard):**

Mil-t-6736 spec.