

View Online at <https://aerobasegroup.com/nsn/5315-01-366-1414>

Shank Diameter:

Between 0.9970 inches and 0.9985 inches

Button Handle Diameter:

Between 1.175 inches and 2.120 inches

Detent Quantity:

2

Actuation Method:

Push button

Grip Length:

Between 3.700 inches and 3.720 inches

Actuation Type:

Push

Hardness Rating:

40.0 rockwell c shank 40.0 rockwell c spindle

Shear Strength:

131000 double pound

Shoulder To Head End Distance:

1.490 inches

Pin Attachment Type:

Link or ring

Detent To Tapered End Distance:

Between 0.860 inches and 0.890 inches

Material:

Steel comp 4130 shank or steel comp 8740 shank steel comp 4130 spindle or steel comp 8740 spindle

Material Specification:

Mil-t-6736 military specification 1st material response shank or mil-s-6758 military specification 2nd material response shank mil-t-6736 military specification 1st material response spindle or mil-s-6758 military specification 2nd material response spindle

Surface Treatment:

Passivate shank passivate spindle

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response shank qq-p-35 federal specification single treatment response spindle

Style Designator:

Button

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A212a0

Mil-std (military Standard):

Mil-t-6736 spec.