

View Online at <https://aerobasegroup.com/nsn/5315-01-366-1417>

Head Diameter:

Between 1.175 inches and 1.330 inches

Shank Diameter:

Between 0.9970 inches and 0.9985 inches

Ring Handle Diameter:

1.640 inches

Detent Quantity:

2

Actuation Method:

Push button

Grip Length:

Between 5.700 inches and 5.720 inches

Actuation Type:

Push

Hardness Rating:

36.0 rockwell c shank and 40.0 rockwell c shank 36.0 rockwell c spindle and 40.0 rockwell c spindle

Shear Strength:

147000 double pounds per square inch

Shoulder To Head End Distance:

2.000 inches

Pin Attachment Type:

Ring

Detent To Tapered End Distance:

Between 0.850 inches and 0.890 inches

Material:

Aluminum alloy 2011 handle or aluminum alloy 2017 handle or aluminum alloy 2024 handle or steel comp 303 handle steel comp 631 shank steel comp 630 spindle aluminum alloy 6061 button or steel comp 303 button or aluminum alloy 2011 button or aluminum alloy 2017 button or aluminum alloy 2024 button steel comp 301 collar or steel comp 302 collar or steel comp 303 collar or steel comp 304 collar steel comp 302 spring

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Style Designator:

Ring handle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A212a0