

View Online at <https://aerobasegroup.com/nsn/5315-01-366-1418>

**Head Diameter:**

Between 1.175 inches and 1.330 inches

**Shank Diameter:**

Between 0.9970 inches and 0.9985 inches

**Ring Handle Diameter:**

1.640 inches

**Detent Quantity:**

2

**Actuation Method:**

Push button

**Grip Length:**

Between 4.200 inches and 4.220 inches

**Actuation Type:**

Push

**Hardness Rating:**

36.0 rockwell c shank and 40.0 rockwell c shank 36.0 rockwell c spindle and 40.0 rockwell c spindle

**Shear Strength:**

147000 double pound

**Shoulder To Head End Distance:**

2.000 inches

**Pin Attachment Type:**

Ring

**Detent To Tapered End Distance:**

Between 0.850 inches and 0.890 inches

**Material:**

Aluminum alloy 2011 handle or aluminum alloy 2017 handle or aluminum alloy 2024 handle or steel comp 303 handle steel comp 631 shank steel comp 630 spindle aluminum alloy 6061 button or steel comp 303 button or aluminum alloy 2011 button or aluminum alloy 2017 button or aluminum alloy 2024 button steel comp 301 collar or steel comp 302 collar or steel comp 303 collar or steel comp 304 collar steel comp 302 spring

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

**Style Designator:**

Ring handle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A212a0