

View Online at <https://aerobasegroup.com/nsn/5315-01-366-1421>

**Head Diameter:**

Between 0.865 inches and 1.045 inches

**Shank Diameter:**

Between 0.7470 inches and 0.7485 inches

**Ring Handle Diameter:**

1.640 inches

**Detent Quantity:**

2

**Actuation Method:**

Push button

**Grip Length:**

Between 2.300 inches and 2.320 inches

**Actuation Type:**

Push

**Hardness Rating:**

40.0 rockwell c shank40.0 rockwell c spindle

**Shear Strength:**

82500 double pound

**Shoulder To Head End Distance:**

1.625 inches

**Pin Attachment Type:**

Link or ring

**Detent To Tapered End Distance:**

Between 0.640 inches and 0.670 inches

**Material:**

Steel comp 630 shank or steel comp 632 shanksteel comp 630 spindle or steel comp 632 spindle

**Material Specification:**

Ams 5643 assn standard 1st material response shank or ams 5657 assn standard 2nd material response shankams 5643 assn standard 1st material response spindle or ams 5657 assn standard 2nd material response spindle

**Surface Treatment:**

Passivate shankpassivate spindle

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response shankqq-p-35 federal specification single treatment response spindle

**Style Designator:**

Ring handle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A212a0