

View Online at <https://aerobasegroup.com/nsn/5315-01-366-3809>

Handle Length:

Between 2.500 inches and 3.100 inches

Shank Diameter:

Between 0.7470 inches and 0.7485 inches

Detent Quantity:

2

Actuation Method:

Push button

Grip Length:

Between 3.900 inches and 3.9020 inches

Actuation Type:

Push

Hardness Rating:

40.0 rockwell c shank 40.0 rockwell c spindle

Shear Strength:

625000 double pound

Shoulder To Head End Distance:

1.720 inches

Pin Attachment Type:

Link and ring

Detent To Tapered End Distance:

Between 0.630 inches and 0.670 inches

Material:

Steel comp 303 handle steel comp 630 shank or steel comp 632 shank steel comp 630 spindle or steel comp 632 spindle steel comp 303 button steel comp 301 collar or steel comp 302 collar or steel comp 303 collar or steel comp 304 collar steel comp 302 ring steel comp 302 spring

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Style Designator:

T handle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A212a0

Mil-std (military Standard):

Mil-p-23460 spec.