

View Online at <https://aerobasegroup.com/nsn/5315-01-366-8833>

**Shank Diameter:**

Between 0.8720 inches and 0.8735 inches

**Button Handle Diameter:**

Between 2.120 inches and 2.250 inches

**Detent Quantity:**

2

**Actuation Method:**

Push button

**Grip Length:**

Between 3.400 inches and 3.420 inches

**Actuation Type:**

Push

**Hardness Rating:**

40.0 rockwell c shank 40.0 rockwell c spindle

**Shear Strength:**

112500 double pound

**Shoulder To Head End Distance:**

1.985 inches

**Pin Attachment Type:**

Link

**Detent To Tapered End Distance:**

Between 0.720 inches and 0.760 inches

**Material:**

Steel comp 630 shank or steel comp 632 shank steel comp 630 spindle or steel comp 632 spindle

**Material Specification:**

Ams 5643 assn standard 1st material response shank or ams 5657 assn standard 2nd material response shank ams 5643 assn standard 1st material response spindle or ams 5657 assn standard 2nd material response spindle

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

**Style Designator:**

Button

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A212a0