

View Online at <https://aerobasegroup.com/nsn/5315-01-367-4896>

Head Diameter:

Between 0.380 inches and 0.450 inches

Handle Length:

Between 1.375 inches and 1.750 inches

Shank Diameter:

Between 0.2470 inches and 0.2485 inches

Detent Quantity:

2

Actuation Method:

Push button

Grip Length:

Between 1.400 inches and 1.420 inches

Actuation Type:

Push

Hardness Rating:

40.0 rockwell c shank40.0 rockwell c spindle

Shear Strength:

9200 double pound

Shoulder To Head End Distance:

1.030 inches

Pin Attachment Type:

Link or ring

Detent To Tapered End Distance:

0.410 inches

Material:

Steel comp 630 shank or steel comp 632 shanksteel comp 630 spindle or steel comp 632 spindle

Material Specification:

Ams5643 assn standard 1st material response shank or ams5657 assn standard 2nd material response shankams5643 assn standard 1st material response spindle or ams5657 assn standard 2nd material response spindle

Surface Treatment:

Passivate shankpassivate spindle

Surface Treatment Specification:

Q-p-35 federal specification single treatment response shankqq-p-35 federal specification single treatment response spindle

Style Designator:

T handle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A212a0