

View Online at <https://aerobasegroup.com/nsn/5315-01-367-4896>

**Head Diameter:**

Between 0.380 inches and 0.450 inches

**Handle Length:**

Between 1.375 inches and 1.750 inches

**Shank Diameter:**

Between 0.2470 inches and 0.2485 inches

**Detent Quantity:**

2

**Actuation Method:**

Push button

**Grip Length:**

Between 1.400 inches and 1.420 inches

**Actuation Type:**

Push

**Hardness Rating:**

40.0 rockwell c shank40.0 rockwell c spindle

**Shear Strength:**

9200 double pound

**Shoulder To Head End Distance:**

1.030 inches

**Pin Attachment Type:**

Link or ring

**Detent To Tapered End Distance:**

0.410 inches

**Material:**

Steel comp 630 shank or steel comp 632 shanksteel comp 630 spindle or steel comp 632 spindle

**Material Specification:**

Ams5643 assn standard 1st material response shank or ams5657 assn standard 2nd material response shankams5643 assn standard 1st material response spindle or ams5657 assn standard 2nd material response spindle

**Surface Treatment:**

Passivate shankpassivate spindle

**Surface Treatment Specification:**

Q-p-35 federal specification single treatment response shankq-p-35 federal specification single treatment response spindle

**Style Designator:**

T handle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A212a0