

View Online at <https://aerobasegroup.com/nsn/5315-01-367-4901>

Head Diameter:

Between 1.070 inches and 1.150 inches

Handle Length:

Between 2.750 inches and 2.875 inches

Shank Diameter:

Between 0.8720 inches and 0.8735 inches

Detent Quantity:

2

Actuation Method:

Push button

Grip Length:

Between 3.000 inches and 3.020 inches

Actuation Type:

Push

Hardness Rating:

40.0 rockwell c shank 40.0 rockwell c spindle

Shear Strength:

112600 double pound

Shoulder To Head End Distance:

1.640 inches

Pin Attachment Type:

Link or ring

Detent To Tapered End Distance:

0.950 inches

Material:

Steel comp 630 shank or steel comp 632 shank steel comp 630 spindle or steel comp 632 spindle

Material Specification:

Ams5643 assn standard 1st material response shank or ams5657 assn standard 2nd material response shank ams5643 assn standard 1st material response spindle or ams5657 assn standard 2nd material response spindle

Surface Treatment:

Passivate shank passivate spindle

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response shank qq-p-35 federal specification single treatment response spindle

Style Designator:

T handle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A212a0