

View Online at <https://aerobasegroup.com/nsn/5315-01-367-4907>

Head Diameter:

Between 0.550 inches and 0.710 inches

Shank Diameter:

Between 0.4345 inches and 0.4360 inches

Ring Handle Diameter:

1.090 inches

Detent Quantity:

2

Actuation Method:

Push button

Grip Length:

Between 1.100 inches and 1.120 inches

Actuation Type:

Push

Hardness Rating:

40.0 rockwell c shank 40.0 rockwell c spindle

Shear Strength:

28000 double pound

Shoulder To Head End Distance:

1.850 inches

Pin Attachment Type:

Link or ring

Detent To Tapered End Distance:

Between 0.340 inches and 0.380 inches

Material:

Steel comp 630 shank or steel comp 632 shank steel comp 630 spindle or steel comp 632 spindle

Material Specification:

Ams5643 assn standard 1st material response shank or ams5657 assn standard 2nd material response shank ams5643 assn standard 1st material response spindle or ams5657 assn standard 2nd material response spindle

Surface Treatment:

Passivate shank passivate spindle

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response shank qq-p-35 federal specification single treatment response spindle

Style Designator:

Ring handle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A212a0