

View Online at <https://aerobasegroup.com/nsn/5315-01-367-4907>

**Head Diameter:**

Between 0.550 inches and 0.710 inches

**Shank Diameter:**

Between 0.4345 inches and 0.4360 inches

**Ring Handle Diameter:**

1.090 inches

**Detent Quantity:**

2

**Actuation Method:**

Push button

**Grip Length:**

Between 1.100 inches and 1.120 inches

**Actuation Type:**

Push

**Hardness Rating:**

40.0 rockwell c shank 40.0 rockwell c spindle

**Shear Strength:**

28000 double pound

**Shoulder To Head End Distance:**

1.850 inches

**Pin Attachment Type:**

Link or ring

**Detent To Tapered End Distance:**

Between 0.340 inches and 0.380 inches

**Material:**

Steel comp 630 shank or steel comp 632 shank steel comp 630 spindle or steel comp 632 spindle

**Material Specification:**

Ams5643 assn standard 1st material response shank or ams5657 assn standard 2nd material response shank ams5643 assn standard 1st material response spindle or ams5657 assn standard 2nd material response spindle

**Surface Treatment:**

Passivate shank passivate spindle

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response shank qq-p-35 federal specification single treatment response spindle

**Style Designator:**

Ring handle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A212a0