

View Online at <https://aerobasegroup.com/nsn/5315-01-367-4914>

Head Diameter:

Between 0.410 inches and 0.590 inches

Shank Diameter:

Between 0.3095 inches and 0.3110 inches

Ring Handle Diameter:

1.060 inches

Detent Quantity:

2

Actuation Method:

Push button

Grip Length:

Between 4.500 inches and 4.520 inches

Actuation Type:

Push

Hardness Rating:

40.0 rockwell c shank 40.0 rockwell c spindle

Shear Strength:

14400 double pound

Shoulder To Head End Distance:

1.650 inches

Pin Attachment Type:

Link or ring

Detent To Tapered End Distance:

Between 0.290 inches and 0.330 inches

Material:

Steel comp 630 shank or steel comp 632 shank steel comp 630 spindle or steel comp 632 spindle

Material Specification:

Ams5643 assn standard 1st material response shank or ams5657 assn standard 2nd material response shank ams5643 assn standard 1st material response spindle or ams5657 assn standard 2nd material response spindle

Surface Treatment:

Passivate shank passivate spindle

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response shank qq-p-35 federal specification single treatment response spindle

Style Designator:

Ring handle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A212a0