

View Online at <https://aerobasegroup.com/nsn/5315-01-367-4915>

Head Diameter:

Between 0.865 inches and 1.045 inches

Shank Diameter:

Between 0.7470 inches and 0.7485 inches

Ring Handle Diameter:

1.640 inches

Detent Quantity:

2

Actuation Method:

Push button

Grip Length:

Between 4.100 inches and 4.120 inches

Actuation Type:

Push

Hardness Rating:

40.0 rockwell c shank40.0 rockwell c spindle

Shear Strength:

82500 double pound

Shoulder To Head End Distance:

2.650 inches

Pin Attachment Type:

Link or ring

Detent To Tapered End Distance:

Between 0.630 inches and 0.670 inches

Material:

Steel comp 630 shank or steel comp 632 shanksteel comp 630 spindle or steel comp 632 spindle

Material Specification:

Ams5643 assn standard 1st material response shank or ams5657 assn standard 2nd material response shankams5643 assn standard 1st material response spindle or ams5657 assn standard 2nd material response spindle

Surface Treatment:

Passivate shankpassivate spindle

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response shankqq-p-35 federal specification single treatment response spindle

Style Designator:

Ring handle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A212a0