

View Online at <https://aerobasegroup.com/nsn/5315-01-367-6430>

**Head Diameter:**

Between 0.510 inches and 0.630 inches

**Shank Diameter:**

Between 0.3720 inches and 0.3735 inches

**Ring Handle Diameter:**

Between 1.000 inches and 1.125 inches

**Detent Quantity:**

2

**Actuation Method:**

Push button

**Grip Length:**

Between 5.400 inches and 5.420 inches

**Actuation Type:**

Push

**Hardness Rating:**

40.0 rockwell c shank 40.0 rockwell c spindle

**Shear Strength:**

20600 double pound

**Shoulder To Head End Distance:**

1.000 inches

**Pin Attachment Type:**

Ring

**Detent To Tapered End Distance:**

0.510 inches

**Material:**

Steel comp 630 shank or steel comp 632 shank steel comp 630 spindle or steel comp 632 spindle

**Material Specification:**

Ams 5643 assn standard 1st material response shank or ams 5657 assn standard 2nd material response shank ams 5643 assn standard 1st material response spindle or ams 5657 assn standard 2nd material response spindle

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

**Style Designator:**

Ring handle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A212a0