

View Online at <https://aerobasegroup.com/nsn/5315-01-367-6446>

Head Diameter:

Between 0.640 inches and 0.755 inches

Handle Length:

Between 2.125 inches and 2.250 inches

Shank Diameter:

Between 0.4970 inches and 0.4985 inches

Detent Quantity:

2

Actuation Method:

Push button

Grip Length:

Between 5.900 inches and 5.920 inches

Actuation Type:

Push

Hardness Rating:

40.0 rockwell c shank40.0 rockwell c spindle

Shear Strength:

36800 double pound

Shoulder To Head End Distance:

1.270 inches

Pin Attachment Type:

Link or ring

Detent To Tapered End Distance:

0.590 inches

Material:

Steel comp 630 shank or steel comp 632 shanksteel comp 630 spindle or steel comp 632 spindle

Material Specification:

Ams5643 assn standard 1st material response shank or ams5657 assn standard 2nd material response shankams5643 assn standard 1st material response spindle or ams5657 assn standard 2nd material response spindle

Surface Treatment:

Passivate shankpassivate spindle

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response shankqq-p-35 federal specification single treatment response spindle

Style Designator:

T handle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A212a0