# NSN 5315-01-367-8763

Quick Release Pin - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5315-01-367-8763

## Head Diameter:

Between 0.640 inches and 0.755 inches

## Shank Diameter:

Between 0.5595 inches and 0.5610 inches

## **Ring Handle Diameter:**

Between 1.000 inches and 1.125 inches

## **Detent Quantity:**

2

## **Actuation Method:**

Push button

Grip Length:

Between 1.600 inches and 1.620 inches

## Actuation Type:

Push

Hardness Rating:

40.0 rockwell c shank40.0 rockwell c spindle

#### Shear Strength:

46000 double pound

## Shoulder To Head End Distance:

1.070 inches

# Pin Attachment Type:

Ring

**Detent To Tapered End Distance:** 

0.660 inches

# Material:

Steel comp 630 shank or steel comp 632 shanksteel comp 630 spindle or steel comp 632 spindle

## Material Specification:

Ams 5643 assn standard 1st material response shank or ams 5657 assn standard 2nd material response shankams 5643 assn standard 1st

material response spindle or ams 5657 assn standard 2nd material response spindle

## Surface Treatment:

Passivate

## **Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

## Style Designator:

Ring handle

Shelf Life:

N/a

# Unit Of Measure:

---

## Demilitarization:

No

## Fiig:

A212a0