

View Online at <https://aerobasegroup.com/nsn/5315-01-367-8784>

**Head Diameter:**

Between 0.680 inches and 0.840 inches

**Shank Diameter:**

Between 0.5595 inches and 0.5610 inches

**Ring Handle Diameter:**

1.160 inches

**Detent Quantity:**

2

**Actuation Method:**

Push button

**Grip Length:**

Between 3.800 inches and 3.820 inches

**Actuation Type:**

Push

**Hardness Rating:**

40.0 rockwell c shank 40.0 rockwell c spindle

**Shear Strength:**

46000 double pound

**Shoulder To Head End Distance:**

2.030 inches

**Pin Attachment Type:**

Link or ring

**Detent To Tapered End Distance:**

Between 0.470 inches and 0.510 inches

**Material:**

Steel comp 630 shank or steel comp 632 shank steel comp 630 spindle or steel comp 632 spindle

**Material Specification:**

Ams5643 assn standard 1st material response shank or ams5657 assn standard 2nd material response shank ams5643 assn standard 1st material response spindle or ams5657 assn standard 2nd material response spindle

**Surface Treatment:**

Passivate shank passivate spindle

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response shank qq-p-35 federal specification single treatment response spindle

**Style Designator:**

Ring handle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A212a0