

View Online at <https://aerobasegroup.com/nsn/5315-01-367-9392>

Head Diameter:

Between 0.390 inches and 0.505 inches

Shank Diameter:

Between 0.3095 inches and 0.3110 inches

Ring Handle Diameter:

Between 1.000 inches and 1.125 inches

Detent Quantity:

2

Actuation Method:

Push button

Grip Length:

Between 2.300 inches and 2.320 inches

Actuation Type:

Push

Hardness Rating:

40.0 rockwell c shank 40.0 rockwell c spindle

Shear Strength:

14400 double pound

Shoulder To Head End Distance:

0.935 inches

Pin Attachment Type:

Ring

Detent To Tapered End Distance:

0.440 inches

Material:

Steel comp 630 shank or steel comp 632 shank steel comp 630 spindle or steel comp 632 spindle

Material Specification:

Ams 5643 assn standard 1st material response shank or ams 5657 assn standard 2nd material response shank ams 5643 assn standard 1st material response spindle or ams 5657 assn standard 2nd material response spindle

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Style Designator:

Ring handle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A212a0