

View Online at <https://aerobasegroup.com/nsn/5315-01-368-2065>

**Shank Diameter:**

Between 0.4345 inches and 0.4360 inches

**Button Handle Diameter:**

Between 0.940 inches and 1.400 inches

**Detent Quantity:**

2

**Actuation Method:**

Push button

**Grip Length:**

Between 0.900 inches and 0.920 inches

**Actuation Type:**

Push

**Hardness Rating:**

40.0 rockwell c shank 40.0 rockwell c spindle

**Shear Strength:**

28000 double pound

**Shoulder To Head End Distance:**

1.160 inches

**Pin Attachment Type:**

Link

**Detent To Tapered End Distance:**

Between 0.340 inches and 0.380 inches

**Material:**

Steel comp 630 shank or steel comp 632 shank steel comp 630 spindle or steel comp 632 spindle

**Material Specification:**

Ams 5643 assn standard 1st material response shank or ams 5657 assn standard 2nd material response shank ams 5643 assn standard 1st material response spindle or ams 5657 assn standard 2nd material response spindle

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

**Style Designator:**

Button

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A212a0