

View Online at <https://aerobasegroup.com/nsn/5315-01-368-5262>

Head Diameter:

Between 0.360 inches and 0.450 inches

Shank Diameter:

Between 0.1870 inches and 0.1885 inches

Detent Quantity:

2

Actuation Method:

Push button

Grip Length:

Between 1.300 inches and 1.320 inches

Actuation Type:

Push

Hardness Rating:

40.0 rockwell c shank40.0 rockwell c spindle

Shear Strength:

5150 double pound

Shoulder To Head End Distance:

1.030 inches

Pin Center To Handle End Distance:

Between 1.200 inches and 1.300 inches

Pin Attachment Type:

Link or ring

Detent To Tapered End Distance:

0.410 inches

Material:

Steel comp 630 shank or steel comp 632 shanksteel comp 630 spindle or steel comp 632 spindle

Material Specification:

Ams 5643 assn standard 1st material response shank or ams 5657 assn standard 2nd material response shankams 5643 assn standard 1st material response spindle or ams 5657 assn standard 2nd material response spindle

Surface Treatment:

Passivate shankpassivate spindle

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response shankqq-p-35 federal specification single treatment response spindle

Style Designator:

L handle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A212a0