

View Online at <https://aerobasegroup.com/nsn/5315-01-368-5286>

**Shank Diameter:**

Between 0.9970 inches and 0.9985 inches

**Detent Quantity:**

2

**Actuation Method:**

Push button

**Grip Length:**

Between 3.700 inches and 3.720 inches

**Actuation Type:**

Push

**Hardness Rating:**

40.0 rockwell c shank 40.0 rockwell c spindle

**Shear Strength:**

147000 double pound

**Shoulder To Head End Distance:**

2.170 inches

**Pin Center To Handle End Distance:**

Between 1.950 inches and 2.900 inches

**Pin Attachment Type:**

Link or ring

**Detent To Tapered End Distance:**

Between 0.860 inches and 0.890 inches

**Material:**

Steel comp 630 shank or steel comp 632 shank steel comp 630 spindle or steel comp 632 spindle

**Material Specification:**

Ams 5643 assn standard 1st material response shank or ams 5657 assn standard 2nd material response shank ams 5643 assn standard 1st material response spindle or ams 5657 assn standard 2nd material response spindle

**Surface Treatment:**

Passivate shank passivate spindle

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response shank qq-p-35 federal specification single treatment response spindle

**Style Designator:**

L handle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A212a0

**Mil-std (military Standard):**

Mil-p-23460 spec.