

View Online at <https://aerobasegroup.com/nsn/5315-01-368-5705>

**Head Diameter:**

Between 0.390 inches and 0.505 inches

**Shank Diameter:**

Between 0.3095 inches and 0.3110 inches

**Detent Quantity:**

2

**Actuation Method:**

Push button

**Grip Length:**

Between 2.200 inches and 2.220 inches

**Actuation Type:**

Push

**Hardness Rating:**

40.0 rockwell c shank 40.0 rockwell c spindle

**Shear Strength:**

14400 double pound

**Shoulder To Head End Distance:**

1.030 inches

**Pin Center To Handle End Distance:**

Between 1.200 inches and 1.300 inches

**Pin Attachment Type:**

Link or ring

**Detent To Tapered End Distance:**

0.440 inches

**Material:**

Steel comp 630 shank or steel comp 632 shank steel comp 630 spindle or steel comp 632 spindle

**Material Specification:**

Ams 5643 assn standard 1st material response shank or ams 5657 assn standard 2nd material response shank ams 5643 assn standard 1st material response spindle or ams 5657 assn standard 2nd material response spindle

**Surface Treatment:**

Passivate shank passivate spindle

**Style Designator:**

L handle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A212a0