

View Online at <https://aerobasegroup.com/nsn/5315-01-368-5711>

**Shank Diameter:**

Between 0.4970 inches and 0.4985 inches

**Detent Quantity:**

2

**Actuation Method:**

Push button

**Grip Length:**

Between 6.200 inches and 6.220 inches

**Actuation Type:**

Push

**Hardness Rating:**

40.0 rockwell c shank 40.0 rockwell c spindle

**Shear Strength:**

36800 double pound

**Shoulder To Head End Distance:**

1.600 inches

**Pin Center To Handle End Distance:**

Between 1.730 inches and 1.850 inches

**Pin Attachment Type:**

Link or ring

**Detent To Tapered End Distance:**

Between 0.430 inches and 0.460 inches

**Material:**

Steel comp 630 shank or steel comp 632 shank steel comp 630 spindle or steel comp 632 spindle

**Material Specification:**

Ams 5643 assn standard 1st material response shank or ams 5657 assn standard 2nd material response shank

**Surface Treatment:**

Passivate shank passivate spindle

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response shank qq-p-35 federal specification single treatment response spindle

**Style Designator:**

L handle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A212a0

**Mil-std (military Standard):**

Mil-p-23460 spec.