

View Online at <https://aerobasegroup.com/nsn/5315-01-368-5715>

Head Diameter:

Between 0.360 inches and 0.450 inches

Shank Diameter:

Between 0.1870 inches and 0.1885 inches

Detent Quantity:

2

Actuation Method:

Push button

Grip Length:

Between 2.100 inches and 2.120 inches

Actuation Type:

Push

Hardness Rating:

40.0 rockwell c shank 40.0 rockwell c spindle

Shear Strength:

5150 double pound

Shoulder To Head End Distance:

1.030 inches

Pin Center To Handle End Distance:

Between 1.200 inches and 1.300 inches

Pin Attachment Type:

Link or ring

Detent To Tapered End Distance:

0.410 inches

Material:

Steel comp 630 shank or steel comp 632 shank steel comp 630 spindle or steel comp 632 spindle

Material Specification:

Ams 5643 assn standard 1st material response shank or ams 557 assn standard 2nd material response shank

Surface Treatment:

Passivate shank passivate spindle

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response shank qq-p-35 federal specification single treatment response spindle

Style Designator:

L handle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A212a0

Mil-std (military Standard):

Mil-p-23460 spec.