

View Online at <https://aerobasegroup.com/nsn/5315-01-368-6185>

Shank Diameter:

Between 0.5595 inches and 0.5610 inches

Detent Quantity:

2

Actuation Method:

Push button

Grip Length:

Between 1.500 inches and 1.520 inches

Actuation Type:

Push

Hardness Rating:

40.0 rockwell c shank 40.0 rockwell c spindle

Shear Strength:

46000 double pound

Shoulder To Head End Distance:

1.600 inches

Pin Center To Handle End Distance:

Between 1.730 inches and 1.860 inches

Pin Attachment Type:

Link or ring

Detent To Tapered End Distance:

Between 0.480 inches and 0.510 inches

Material:

Steel comp 630 shank or steel comp 632 shank steel comp 630 spindle or steel comp 632 spindle

Material Specification:

Ams 5643 assn standard 1st material response shank or ams 5657 assn standard 2nd material response shank ams 5643 assn standard 1st material response spindle or ams 5657 assn standard 2nd material response spindle

Surface Treatment:

Passivate shank passivate spindle

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response shank qq-p-35 federal specification single treatment response spindle

Style Designator:

L handle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A212a0

Mil-std (military Standard):

Mil-p-23460 spec.