

View Online at <https://aerobasegroup.com/nsn/5315-01-369-4915>

Handle Length:

Between 2.220 inches and 2.345 inches

Shank Diameter:

Between 0.4970 inches and 0.4985 inches

Detent Quantity:

2

Actuation Method:

Push button

Grip Length:

Between 9.800 inches and 9.820 inches

Actuation Type:

Push

Hardness Rating:

36.0 rockwell c shank and 40.0 rockwell c shank 36.0 rockwell c spindle and 40.0 rockwell c spindle

Shear Strength:

36800 double pound

Shoulder To Head End Distance:

1.600 inches

Pin Attachment Type:

Link or ring

Detent To Tapered End Distance:

Between 0.430 inches and 0.460 inches

Material:

Steel comp 4130 shank or steel comp 8740 shank steel comp 4130 spindle or steel comp 8740 spindle

Material Specification:

Mil-t-6736 military specification 1st material response shank or mil-s-6758 military specification 2nd material response shank mil-t-6736 military specification 1st material response spindle or mil-s-6758 military specification 2nd material response spindle

Surface Treatment:

Cadmium shank and chromate shank cadmium spindle or chromate spindle

Surface Treatment Specification:

Qq-p-416, type 2, cl 2 federal specification single treatment response shank qq-p-416, type 2, cl 2 federal specification single treatment response spindle

Style Designator:

T handle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A212a0

Mil-std (military Standard):

Mil-t-6736 spec.