

View Online at <https://aerobasegroup.com/nsn/5315-01-369-6156>

First End Style:

Slotted

Second End Style:

Square

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

0.513 inches

Hole Arrangement Style:

Both end drilled

First Hole Diameter:

Between 0.125 inches and 0.128 inches

Second Hole Diameter:

Between 0.125 inches and 0.128 inches

Distance From Centerline Of Hole To End Of Pin:

2.523 inches

Center To Center Distance Between Holes:

0.500 inches

Pinlength:

3.310 inches

Pindiameter:

Between 0.4335 inches and 0.4375 inches

First End Slot Width:

Between 0.169 inches and 0.175 inches

First End Slot Depth:

2.485 inches

Second End Relationship With First End:

Not identical

Thread Size:

0.4375 inches

First End Location:

Unthreaded end

Special Features:

Prime exposed surfaces with mil-p-23377 epoxy primer .0006 to .0009 thk. Apply 2 coats mil-c-83286 black urethane, color

Material:

Steel comp 4130

Material Specification:

Mil-s-6758 military specification all material responses

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416 federal specification all treatment responses

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A212a0

Mil-std (military Standard):

Mil-s-6758 spec.