

View Online at <https://aerobasegroup.com/nsn/5315-01-369-6156>

**First End Style:**

Slotted

**Second End Style:**

Square

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

0.513 inches

**Hole Arrangement Style:**

Both end drilled

**First Hole Diameter:**

Between 0.125 inches and 0.128 inches

**Second Hole Diameter:**

Between 0.125 inches and 0.128 inches

**Distance From Centerline Of Hole To End Of Pin:**

2.523 inches

**Center To Center Distance Between Holes:**

0.500 inches

**Pinlength:**

3.310 inches

**Pindiameter:**

Between 0.4335 inches and 0.4375 inches

**First End Slot Width:**

Between 0.169 inches and 0.175 inches

**First End Slot Depth:**

2.485 inches

**Second End Relationship With First End:**

Not identical

**Thread Size:**

0.4375 inches

**First End Location:**

Unthreaded end

**Special Features:**

Prime exposed surfaces with mil-p-23377 epoxy primer .0006 to .0009 thk. Apply 2 coats mil-c-83286 black urethane, color

**Material:**

Steel comp 4130

**Material Specification:**

Mil-s-6758 military specification all material responses

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Qq-p-416 federal specification all treatment responses

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A212a0

**Mil-std (military Standard):**

Mil-s-6758 spec.