

View Online at <https://aerobasegroup.com/nsn/5315-01-369-6788>

Head Diameter:

Between 0.890 inches and 0.960 inches

Shank Diameter:

Between 0.7470 inches and 0.7485 inches

Ring Handle Diameter:

Between 1.312 inches and 1.500 inches

Detent Quantity:

2

Actuation Method:

Push button

Grip Length:

Between 6.000 inches and 6.020 inches

Actuation Type:

Push

Hardness Rating:

40.0 rockwell c shank40.0 rockwell c spindle

Shear Strength:

82500 double pound

Shoulder To Head End Distance:

1.250 inches

Pin Attachment Type:

Ring

Detent To Tapered End Distance:

0.790 inches

Material:

Steel comp 630 shank or steel comp 632 shanksteel comp 630 spindle or steel comp 632 spindle

Material Specification:

Ams 5643 assn standard 1st material response shank or ams 5657 assn standard 2nd material response shankams 5643 assn standard 1st material response spindle or ams 5657 assn standard 2nd material response spindle

Surface Treatment:

Passivate shankpassivate spindle

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response shankqq-p-35 federal specification single treatment response spindle

Style Designator:

Ring handle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A212a0