

View Online at <https://aerobasegroup.com/nsn/5315-01-369-9137>

**Handle Length:**

Between 1.750 inches and 2.000 inches

**Shank Diameter:**

Between 0.3720 inches and 0.3745 inches

**Detent Quantity:**

2

**Actuation Method:**

Push button

**Grip Length:**

Between 8.000 inches and 8.020 inches

**Actuation Type:**

Push

**Hardness Rating:**

40.0 rockwell c shank 40.0 rockwell c spindle

**Shoulder To Head End Distance:**

1.550 inches

**Pin Attachment Type:**

Ring or hook

**Detent To Tapered End Distance:**

0.490 inches

**Material:**

Steel comp 630 shank or steel comp 632 shank steel comp 630 spindle or steel comp 632 spindle

**Material Specification:**

Ams 5643 assn standard 1st material response shank or ams 5520 assn standard 2nd material response shank or ams 5657 assn standard 2nd material response shank ams 5643 assn standard 1st material response spindle or ams 5520 assn standard 2nd material response spindle or ams 5657 assn standard 2nd material response spindle

**Surface Treatment:**

Passivate shank passivate spindle

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response shank qq-p-35 federal specification single treatment response spindle

**Style Designator:**

T handle

**Specification Data:**

80205-nas1336 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A212a0