NSN 5315-01-370-7212

Headless Shoulder Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-01-370-7212 First End Style: Slotted **Second End Style:** Square **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 8.89 millimeters **Shank Length:** 11.94 millimeters **Shoulder Width Across Flats:** 4.75 millimeters **Shank Diameter:** Between 1.90 millimeters and 2.16 millimeters **Overall Length:** Between 21.34 millimeters and 21.84 millimeters **Undercut Diameter:** Between 3.30 millimeters and 3.58 millimeters **Undercut Width:** Between 0.63 millimeters and 0.89 millimeters **Second Undercut Width:** 2.16 millimeters **Second Undercut Diameter:** Between 3.05 millimeters and 3.31 millimeters **Internal Drive Style:** Slot First End Slot Width: Between 0.76 millimeters and 1.02 millimeters First End Slot Depth: Between 1.27 millimeters and 1.77 millimeters Second End Relationship With First End: Not identical **Thread Size:** 0.112 inches **Second Shank Diameter:** 3.45 millimeters **First End Location:** Slot end First End Outer Radius: Between 3.05 millimeters and 3.31 millimeters

NSN 5315-01-370-7212

Headless Shoulder Pin - Page 2 of 2



Second Shank Length:
14.1 millimeters
Material:
Steel comp 303
Style Designator:
Undercut
Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No Fiig: A212a0