

View Online at <https://aerobasegroup.com/nsn/5315-01-370-9292>

Head Diameter:

Between 0.485 inches and 0.515 inches

Shank Diameter:

0.430 inches

Ring Handle Diameter:

Between 0.938 inches and 1.062 inches

Detent Quantity:

2

Actuation Method:

Push button

Grip Length:

Between 3.500 inches and 3.520 inches

Actuation Type:

Push

Hardness Rating:

40.0 rockwell c shank 40.0 rockwell c spindle

Shear Strength:

5000 double pound

Shoulder To Head End Distance:

0.562 inches

Pin Attachment Type:

Ring

Detent To Tapered End Distance:

0.390 inches

Material:

Steel comp 630 shank or steel comp 632 shank steel comp 630 spindle or steel comp 632 spindle

Material Specification:

Ams 5643 assn standard 1st material response shank or ams 5657 assn standard 2nd material response shank ams 5643 assn standard 1st material response spindle or ams 5657 assn standard 2nd material response spindle

Surface Treatment:

Passivate shank passivate spindle

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response shank qq-p-35 federal specification single treatment response spindle

Style Designator:

Ring handle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A212a0