NSN 5315-01-372-7340

Headless Shoulder Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-01-372-7340

| First End Style: |
|--|
| Chamfered |
| Second End Style: |
| Radius |
| Thread Class: |
| 2a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| 0.295 inches |
| Shank Length: |
| 0.950 inches |
| Shank Diameter: |
| Between 0.184 inches and 0.185 inches |
| Overall Length: |
| 2.495 inches |
| End Application: |
| Target pod |
| Second End Corner Radius: |
| 0.450 inches |
| Thready Qty Per Inch (tpi): |
| 32 |
| Second End Relationship With First End: |
| Not identical |
| Thread Size: |
| 0.190 inches |
| First End Location: |
| Pointed end |
| First End Taper Angle: |
| 25.0 degrees |
| First End Tip Radius: |
| 0.050 inches |
| Second Shank Length: |
| Between 1.540 inches and 1.600 inches |
| Special Features: |
| Used on pin, guide-roll to nose interface |
| Material: |
| Steel comp 303 |
| Material Specification: |
| Astm a581 assn standard 1st material response or astm a582 assn standard 2nd material response |
| Style Designator: |
| |

Shoulder

NSN 5315-01-372-7340

Headless Shoulder Pin - Page 2 of 2



Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

Yes - demil/mli

Fiig:

A212a0