

View Online at <https://aerobasegroup.com/nsn/5315-01-373-9091>

**Shank Diameter:**

Between 0.4970 inches and 0.4985 inches

**Detent Quantity:**

2

**End Application:**

C17a serd 230022

**Grip Length:**

Between 1.800 inches and 1.820 inches

**Actuation Type:**

Push

**Hardness Rating:**

40.0 rockwell c shank40.0 rockwell c spindle

**Shoulder To Head End Distance:**

1.600 inches

**Pin Center To Handle End Distance:**

0.500 inches

**Detent To Tapered End Distance:**

Between 0.420 inches and 0.460 inches

**Special Features:**

Altered item made fr ms17986c818: remove and discard "s" hook fr quick -release pin

**Material:**

Steel comp 630 shank or steel comp 632 shanksteel comp 630 spindle or steel comp 632 spindle

**Material Specification:**

Ams 5643 assn standard 1st material response shank or ams 5657 assn standard 2nd material response shankams 5643 assn standard 1st material response spindle or ams 5657 assn standard 2nd material response spindle

**Surface Treatment:**

Passivate shankpassivate spindle

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response shankqq-p-35 federal specification single treatment response spindle

**Style Designator:**

L handle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A212a0