

View Online at <https://aerobasegroup.com/nsn/5315-01-373-9092>

**Shank Diameter:**

Between 0.7470 inches and 0.7485 inches

**Button Handle Diameter:**

Between 1.790 inches and 1.900 inches

**Detent Quantity:**

2

**End Application:**

C17a serd 230022

**Grip Length:**

Between 2.400 inches and 2.420 inches

**Actuation Type:**

Push

**Hardness Rating:**

40.0 rockwell c shank 40.0 rockwell c spindle

**Shoulder To Head End Distance:**

1.680 inches

**Detent To Tapered End Distance:**

Between 0.630 inches and 0.670 inches

**Special Features:**

Altered item made fr ms17984c1224: remove and discard "s" hook fr quick -release pin

**Material:**

Steel comp 630 shank or steel comp 632 shank steel comp 630 spindle or steel comp 632 spindle

**Material Specification:**

Ams 5643 assn standard 1st material response shank or ams 5657 assn standard 2nd material response shank ams 5643 assn standard 1st material response spindle or ams 5657 assn standard 2nd material response spindle

**Surface Treatment:**

Passivate shank passivate spindle

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response shank qq-p-35 federal specification single treatment response spindle

**Style Designator:**

Button

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A212a0