

View Online at <https://aerobasegroup.com/nsn/5315-01-373-9092>

Shank Diameter:

Between 0.7470 inches and 0.7485 inches

Button Handle Diameter:

Between 1.790 inches and 1.900 inches

Detent Quantity:

2

End Application:

C17a serd 230022

Grip Length:

Between 2.400 inches and 2.420 inches

Actuation Type:

Push

Hardness Rating:

40.0 rockwell c shank 40.0 rockwell c spindle

Shoulder To Head End Distance:

1.680 inches

Detent To Tapered End Distance:

Between 0.630 inches and 0.670 inches

Special Features:

Altered item made fr ms17984c1224: remove and discard "s" hook fr quick -release pin

Material:

Steel comp 630 shank or steel comp 632 shank steel comp 630 spindle or steel comp 632 spindle

Material Specification:

Ams 5643 assn standard 1st material response shank or ams 5657 assn standard 2nd material response shank ams 5643 assn standard 1st material response spindle or ams 5657 assn standard 2nd material response spindle

Surface Treatment:

Passivate shank passivate spindle

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response shank qq-p-35 federal specification single treatment response spindle

Style Designator:

Button

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A212a0