

View Online at <https://aerobasegroup.com/nsn/5315-01-374-0448>

Shank Diameter:

Between 0.300 inches and 0.390 inches

Button Handle Diameter:

Between 0.875 inches and 1.135 inches

Detent Quantity:

2

Actuation Method:

Push button

Grip Length:

Between 3.493 inches and 3.513 inches

Actuation Type:

Push

Hardness Rating:

40.0 rockwell c shank 40.0 rockwell c spindle

Shear Strength:

20600 double pounds per square inch

Shoulder To Head End Distance:

1.040 inches

Pin Attachment Type:

Link or ring

Detent To Tapered End Distance:

Between 0.325 inches and 0.365 inches

Special Features:

Slot on grip 1.730 slot on grip 1.730 in. Min 1.750 in. Max, thickness 0.064 min 0.068 depth 0.060 min 0.080 max

Material:

Steel comp 630 shank or steel comp 632 shank steel comp 630 spindle or steel comp 632 spindle

Material Specification:

Ams5643 assn standard 1st material response shank or ams5657 assn standard 2nd material response shank ams5643 assn standard 1st material response spindle or ams5657 assn standard 2nd material response spindle

Surface Treatment:

Passivate shank passivate spindle

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response shank qq-p-35 federal specification single treatment response spindle

Style Designator:

Button

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A212a0