

View Online at <https://aerobasegroup.com/nsn/5315-01-374-9503>

First End Style:

Chamfered

Second End Style:

Square

Shank Length:

2.620 inches

Shank Diameter:

Between 0.488 inches and 0.498 inches

Overall Length:

7.875 inches

Undercut Diameter:

Between 0.455 inches and 0.475 inches

Undercut Width:

2.500 inches

First End Taper Length:

0.065 inches

Second End Relationship With First End:

Not identical

Hardness Rating:

36.0 rockwell c and 43.0 rockwell c

Second Shank Diameter:

Between 0.360 inches and 0.370 inches

First End Location:

Long end

First End Taper Angle:

Between 40.0 degrees and 50.0 degrees

Second Shank Length:

0.250 inches

Special Features:

Cut out on second shank length 0.375 in. Long 0.340 in. Min. 0.360 in. Max. Deep

Material:

Steel comp 4130 or steel comp 4137 or steel comp 4140 or steel comp 8630 or steel comp 8637 or steel comp 8640

Material Specification:

Astm a322 assn standard 1st material response or astm a322 assn standard 2nd material response or astm a322 assn standard 3rd material response or astm a322 assn standard 4th material response or astm a322 assn standard 5th material response or astm a322 assn standard 6th material response

Surface Treatment:

Nickel

Surface Treatment Specification:

Mil-c-26074, cl 2, gr a military specification single treatment response

Style Designator:

Undercut

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A212a0

Mil-std (military Standard):

Mil-c-26074 spec.