

View Online at <https://aerobasegroup.com/nsn/5315-01-374-9503>

**First End Style:**

Chamfered

**Second End Style:**

Square

**Shank Length:**

2.620 inches

**Shank Diameter:**

Between 0.488 inches and 0.498 inches

**Overall Length:**

7.875 inches

**Undercut Diameter:**

Between 0.455 inches and 0.475 inches

**Undercut Width:**

2.500 inches

**First End Taper Length:**

0.065 inches

**Second End Relationship With First End:**

Not identical

**Hardness Rating:**

36.0 rockwell c and 43.0 rockwell c

**Second Shank Diameter:**

Between 0.360 inches and 0.370 inches

**First End Location:**

Long end

**First End Taper Angle:**

Between 40.0 degrees and 50.0 degrees

**Second Shank Length:**

0.250 inches

**Special Features:**

Cut out on second shank length 0.375 in. Long 0.340 in. Min. 0.360 in. Max. Deep

**Material:**

Steel comp 4130 or steel comp 4137 or steel comp 4140 or steel comp 8630 or steel comp 8637 or steel comp 8640

**Material Specification:**

Astm a322 assn standard 1st material response or astm a322 assn standard 2nd material response or astm a322 assn standard 3rd material response or astm a322 assn standard 4th material response or astm a322 assn standard 5th material response or astm a322 assn standard 6th material response

**Surface Treatment:**

Nickel

**Surface Treatment Specification:**

Mil-c-26074, cl 2, gr a military specification single treatment response

**Style Designator:**

Undercut

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A212a0

**Mil-std (military Standard):**

Mil-c-26074 spec.